



RACO[®]


A Division of Hubbell Incorporated (Delaware)

Metal Clad and Armored Cable Connectors


PATENTED - SNAP-IN DESIGN FOR LOWER INSTALLED COST



1/2"
Redi-Loc[®]
2700



1/2"
Redi-Loc[®]
2700AJ
(Expanded Range)



3/4"
Redi-Loc[®]
2701

Applications

- RACO is pleased to announce the availability of a new family of connectors for use with MCI, AC and HCF Cable.

Product Features

Redi-Loc[®] Connectors (2700, 2700AJ and 2701)

- Patented snap-in design - MCI, AC and HCF Cable can be securely installed in outlet boxes or enclosures in seconds, **without tools or locknuts.**
- Redi-Loc[®] Connectors cut installation time by 33% over competing termination methods.
- Compact single unit design - no need to worry about loose components or fumbling with protruding hardware.
- Snaps tightly into the knockout - no need to worry about a loose connection.
- Reusable design - installation can be reversed just as easily as it was originally installed.
- Integral red insuliner - provides for maximum wire protection and liner visibility for inspecting authorities.
- Durable all steel construction.
- Zinc electroplated - for corrosion protection.


TRADITIONAL SADDLE CLAMP DESIGN



1/2"
Connector
2800



3/4"
Connector
2801



1/2"
Duplex Connector
2715

Product Features

(2800, 2801 and 2715)

- Easy to install, just tilt, insert and snap into the knockout.
- Tri-head screw/clamp design - connector can be installed by using a slotted, #2 Phillips or #2 Robertson head screwdriver.
- Integral insuliner - provides for maximum wire protection.
- Durable all-steel construction.
- Zinc electroplated - for corrosion protection.




SPECIFICATIONS

ORDERING INFORMATION FOR MCI, AC AND HCF CABLES - STEEL					
Catalog No.	Trade Size	Cable Size	Unit Ctn. Qty.	Ship Ctn. Qty.	Weight Per 100
2700	1/2"	MCI Cable .434"-.530" Alum or .430" - .530" Steel, Armored Cable (AC) 14/2 (.430) to 12/3 Alum. and Steel	50	500	3.5
2700AJ	1/2"	MCI Cable .475"-.575" Alum. & Steel, Armored Cable (AC) 14/2 (.475) to 12/4 Alum. and Steel	50	500	3.5
2701	3/4"	MCI Cable .590"-.680" Alum or .565" - .659" Steel, Armored Cable (AC) 10/3 (.590) to 8/3 Alum. and Steel	25	250	5.3
2800	1/2"	MCC (ALS) .390"-.470" MCI Cable .500"-.580" Aluminum .460"-.570" Steel Armored Cable Aluminum 14-2 (.475) to 12-4, Steel 14-2 (.475) to 10-3	50	500	8.1
2801	3/4"	MCI Cable .640"-.725" Aluminum .590"-.710" Steel Armored Cable Aluminum 10-4 (.590) to 8-4 Steel 10-4 (.590) to 6-3	25	250	12.2
2715	1/2"	MCI Cable .450"-.545" Alum .425" - .550" Steel, MCC Cable .380"-.550"Alum. Armored Cable (AC) 14/2 to 12/3 w/Grnd Alum. and Steel	25	250	12.5

SELECTION CHART*						
Cable Type	2700	2700AJ	2701	2800	2801	2715
AC Steel	14/2, 14/3, 14/4, 12/2, 12/3	14/2, 14/3, 14/4, 14/5	12/5, 10/2, 10/3, 10/4	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2, 10/3	10/4, 10/5, 8/3, 8/4, 6/3	14/2, 14/3, 14/4, 12/2, 12/3
HCF Steel Health Care Facilities	14/2, 14/3, 12/2, 12/3	14/2, 14/3, 12/2, 12/3	12/3, 12/5, 10/2, 10/3, 10/4 w/Grnd	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2		14/2, 14/3, 14/4, 12/2, 12/3
AC Aluminum	14/2, 14/3, 14/4, 12/2, 12/3	14/2, 14/3, 14/4, 14/5, 12/2, 12/3, 10/2	12/5, 10/2, 10/3, 10/4	14/2, 14/3, 14/4, 12/2, 12/3, 12/4	8/2, 8/3, 8/4, 10/4	14/2, 14/3, 12/2, 12/3
MCI Steel	14/2, 14/3, 12/2	14/3, 14/4, 12/2, 12/3, 10/2	12/4, 12/5, 12/6, 10/2, 10/3	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2	12/4, 10/3, 10/4, 8/2, 8/3	14/2, 14/3, 12/2, 12/3
MCI Aluminum Interlocked	14/2, 14/3, 12/2	14/3, 14/4, 12/2, 12/3, 10/2	12/4, 12/5, 12/6, 10/2, 10/3	14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2	12/4, 10/3, 10/4, 8/2	14/2, 14/3, 12/2, 12/3
MCC Aluminum				14/2, 14/3, 14/4, 12/2, 12/3, 12/4, 10/2, 10/3		

* Gage sizes vary. Refer to cable manufacturers catalogs for exact diameters.

DIMENSIONS				
Catalog No.	Trade Size	Overall Length	Body Width	Throat I.D.
2700	1/2"	1.070"	.700"	.375"
2700AJ	1/2"	1.070"	.700"	.375"
2701	3/4"	1.070"	.888"	.500"
2715	1/2"	1.563"	1.719"	.563"
2800	1/2"	1.470"	1.000"	.375"
2801	3/4"	1.660"	1.325"	.562"



REFERENCE DATA

U.S. Patents 5,731,543 & 6,020,557. Mexican Patent 201,635. Other Patents Pending.



RACO

A Division of Hubbell Incorporated (Delaware)

Distributed By:

3902 W. Sample St. P.O. Box 4002
South Bend, IN 46634-4002
TEL: 574-234-7151 FAX: 574-234-0625
www.hubbell-raco.com

HUBBELL ELECTRICAL PRODUCTS

A Division of Hubbell Incorporated (Delaware)

©2003 Hubbell Incorporated (Delaware)